

LIQUID-TIGHT FITTINGS


STRAIGHT NON-METALLIC CONNECTORS

For use with non-metallic liquid-tight conduit, type B only and flexible non-metallic tubing. Produced from UV rated plastic for long outdoor life.



NMLT50

CATALOG NUMBER	UPC/DCI/NAED MFG#01 8897	TRADE SIZE	K.O. SIZE	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
NMLT38	54380	3/8	1/2	25	100	1.425	.535	1.421
NMLT50	54500	1/2	1/2	25	100	1.425	.535	1.421
NMLT75	54750	3/4	3/4	10	50	1.475	.550	1.583
NMLT100	54100	1	1	5	25	1.950	.670	1.925
NMLT125	04223	1-1/4	1-1/4	5	25	2.217	.645	2.418
NMLT150	04222	1-1/2	1-1/2	2	10	2.155	.660	2.700
NMLT200	04221	2	2	2	10	2.400	.670	3.360



E60812 LR49636

Add suffix "BL" to Catalog # when ordering in black, for example NMLT50BL.



INSTALLATION INSTRUCTIONS

Arlington Industries' reusable Liquid-Tight Fittings may be secured to conduit while fully assembled because of our no-spin ferrule. Simply loosen nut, and screw onto conduit. A positive liquid-tight seal is provided by our pressure sensitive internal gland when the nut is tightened. A liquid tight seal is also assured between the fitting and box by a sealing ring.

-- Select to Jump --

[Products Index](#) [Table of Contents](#) [Next](#)



Arlington Industries, Inc.

800-233-4717 | FAX 570-562-0646 | 1 STAUFFER INDUSTRIAL PARK. SCRANTON, PA 18517
[CONTACT US](#) Copyright © 2000 All rights reserved. Revised: October 07, 2003.