

Threaded Rigid Conduit and IMC Couplings and Connectors

Catalog No.	Size (In.)	Dimensions in Inches			Wt. Lbs. Per 100	Ctn. Qty.	Std. Pkg.
		A	B	C			
Three Piece Union- Concrete Tight							
EC-50	1/2	1-7/16	1-7/16	—	16.5	10	100
EC-75	3/4	1-9/16	1-9/16	—	24.0	10	100
EC-100	1	1-11/16	2	—	58.0	5	25
EC-125	1-1/4	2-1/8	2-7/16	—	98.0	5	25
EC-150	1-1/2	2-3/16	2-11/16	—	134.0	5	25
EC-200	2	2-7/16	3-1/4	—	198.0	5	25
EC-250	2-1/2	2-5/8	3-1/16	—	255.0	2	10
EC-300	3	2-5/8	4-5/8	—	394.0	1	10
EC-350	3-1/2	2-5/8	5-3/16	—	380.0	1	5
EC-400	4	3-7/16	5-11/16	—	700.0	1	5
EC-500	5	3-1/2	6-15/16	—	788.0	1	2
EC-600	6	3-1/2	8-1/8	—	825.0	—	1
90° Female Gasketed Pulling Elbows- Watertight - Malleable Iron							
FFL-50	1/2	1-3/16	—	—	31.0	10	100
FFL-75	3/4	1-11/32	—	—	46.0	10	50
FFL-100	1	1-19/32	—	—	76.0	5	25
FFL-125	1-1/4	2-1/4	—	—	120.0	5	25
FFL-150	1-1/2	2-9/16	—	—	160.0	5	10
FFL-200	2	3-3/16	—	—	293.0	5	10
90° Male to Female Gasketed Pulling Elbows- Watertight- Malleable Iron							
MFL-50	1/2	1-3/16	1-7/16	15/32	36.0	10	100
MFL-75	3/4	1-11/32	1-17/32	1/2	55.0	10	50
MFL-100	1	1-19/32	1-3/4	9/16	90.0	5	25
MFL-125	1-1/4	2-1/4	3-1/8	7/8	141.0	5	25
MFL-150	1-1/2	2-9/16	3-7/16	7/8	192.0	5	10
MFL-200	2	3-3/16	4-3/16	1	335.0	5	10
90° Female Pulling Elbows††- Malleable Iron							
PFFL-50	1/2	2-7/16	1-1/8	—	49.0	10	100
PFFL-75	3/4	2-23/32	1-3/8	—	76.0	5	50
PFFL-100	1	3-1/4	1-23/32	—	121.0	5	25
90° Female Elbows††- Malleable Iron							
LF90-50	1/2	1-1/2	—	—	39.0	10	100
LF90-75	3/4	1-11/16	—	—	53.0	10	100
90° Male to Female Long Bushed Elbows††- Malleable Iron							
LMFL90-50	1/2	1-3/4	1-25/32	19/32	32.5	25	100
LMFL90-75	3/4	2-1/4	2-9/32	11/16	50.0	5	25
LMFL90-100	1	2-21/32	2-11/16	3/4	87.0	5	25
LMFL90-125	1-1/4	3-5/16	3-11/32	1	126.0	5	20
LMFL90-150	1-1/2	3-15/16	3-31/32	1-1/16	170.0	5	10
LMFL90-200	2	4	4	1-1/16	410.0	1	10
90° Male to Female Short Bushed Elbows††- Malleable Iron							
LMF90-50	1/2	1-1/4	1-13/32	1/2	23.0	25	100
LMF90-75	3/4	1-7/16	1-11/16	13/16	36.0	25	100
LMF90-100	1	1-21/32	1-15/16	1	58.0	10	100
90° Male to Female Short Box Connectors††- Malleable Iron							
LMF90-50L	1/2	1-1/4	1-3/32	7/16	26.0	25	50
LMF90-75L	3/4	1-7/16	1-1/4	7/16	34.0	25	50

†† Not CSA Certified.